

## SCREW AIR COMPRESSOR TECHNICAL SPECIFICATIONS

### LUPAMAT LKV 45/7,5 D PREMIUM

DESCRIPTION	SPECIFICATIONS
Compressor Type	Oil Injected Screw Air Compressor
Max. Pressure	7,5 bar
Free Air Delivery (at 7,5 bar)	*8,54 m <sup>3</sup> /min.
Shaft Power (at 7,5 bar)	51 kW
Max. Ambient Temperature	40°C
Control System	Microprocessor
Electric Motor	45 kW/60hp; 2 Pole (2980 rpm); 400V; 50Hz; IP55; IE4 Class; F Insulation; B35 Built; SF Motor
Cooling System	Air Cooling with Axial Fan
Fan Motor & Capacity	1,5 kW; (1435 rpm); 400V; 50Hz --- 7840/289 (m <sup>3</sup> /h)/Pa
Airend	SCA14 GR – TMC
Hydraulic Connections	VITILLO
Oil & Air Filters	MANN+HUMMEL
Cooler	AKG
Suction Control Group	EAGURT
Electric Components	SCHNEIDER / MITSUBISHI
Coupling	REXNORD / DODGE
R.P.M of Airend	4078 rpm
Drive System	Direct Driven with Coupling
Outlet Connection & Cable Size	1 ½" --- (3x35)+16mm <sup>2</sup>
Length	1850 mm
Width	1250 mm
Height	1635 mm
Weight	1475 kg
Noise Level	**71 dB (A)
Max. Oil Content	2-3 ppm.(mg/m <sup>3</sup> )
Warranty	Two Years Against Manufacturing Defects
Shipping Weight & Dimension	1505 kg. – 1950 x 1350 x 1785 mm.

\* FAD performance measured according to ISO 1217, Ed. 4, Annex C-2009

\*\* Noise Level measured to ISO 2151, Tolerance ± 3 dB (A)

Lupamat reserves the right to make alterations on given data & compressor design without prior notice

# Lupamat

Makina Sanayii A.Ş.

