

SCREW AIR COMPRESSOR TECHNICAL SPECIFICATIONS

LUPAMAT LKV 37/7,5 DHK PLUS

DESCRIPTION	SPECIFICATIONS
Compressor Type	Oil Injected Screw Air Compressor
Max. Pressure	7,5 bar
Free Air Delivery (at 7,5 bar)*	6,06 m ³ /min
Min. Pressure	5 bar
Min. Free Air Delivery	3,1 m ³ /min
Shaft Power (at 7,5 bar)	37 kW
Max. Ambient Temperature	40°C
Electric Motor	37 kW / 50 hp; 2 Pole (2960 rpm); 400V; 50Hz; IP55; F Insulation; IE3 Class; B35 Built
Cooling System	Air Cooling with Axial Fan
Fan Motor & Capacity	1,1 kW; (1435 rpm); 400V; 50Hz --- 6235/249 (m ³ /h)/Pa
Airend	SCA13 – TMC
Hydraulic Connections	GURSAN / VITILLO
Cooler	AKG
Oil & Air Filters	MANN+HUMMEL
Suction Control Group	EAGURT
Electric Components	mitsubishi / SCHNEIDER
Variable Frequency Drive(VFD)	MITSUBISHI / YASKAWA
Coupling	DODGE / REXNORD
R.P.M of Airend	4608 rpm
Driving	Direct Driven with Frequency Controller
Outlet Connection & Cable Size	1 ¼" --- (3x25)+16 mm ²
Dimensions (W – L – H)	1600 x 1100 x 1485 mm
Weight	1550 kg
Separator Tank	CE Certified
Noise Level**	70 dB (A)
Max. Oil Content	2-3 ppm.(mg/m ³)
Warranty	Two Years Against Manufacturing Defects
Shipping Weight & Dimension	1580 kg – 1700 x 1200 x 1650 mm

* FAD performance measured according to ISO 1217, Annex E-2009

** Noise Level measured to ISO 2151, Tolerance ± 3 dB (A)

-Lupamat reserves the right to make alterations on given data & compressor design without prior notice.

Lupamat

Makina Sanayii A.Ş.

