

SCREW AIR COMPRESSOR TECHNICAL SPECIFICATIONS

LUPAMAT LKV 18.5/7.5 DHK PREMIUM

DESCRIPTION	SPECIFICATIONS
Compressor Type	Oil Injected Screw Air Compressor
Max. Pressure	7,5 bar
Free Air Delivery (at 7,5 bar)	*3,6 m ³ /min
Min. Pressure	5 bar
Min. Free Air Delivery	1,59 m ³ /min.
Shaft Power (at 7,5 bar)	20 kW
Max. Ambient Temperature	40°C
Electric Motor	18,5 kW / 25 hp; 2 Pole (2960rpm); 400V; 50Hz; IP55; F Insulation; B35 Built; IE4 Class; SF Motor
Cooling System	Air Cooling with Axial Fan
Fan Motor & Capacity	0,46 kW; (1365 rpm); 400V; 50Hz --- 4800/125 (m ³ /h)/Pa
Airend	VMX37 D – AERZEN
Hydraulic Connections	VITILLO
Cooler	AKG
Oil & Air Filters	MANN+HUMMEL
Suction Control Group	EAGURT
Electrical Components	SCHNEIDER / MITSUBISHI
Coupling	REXNORD / DODGE
Variable Frequency Drive(VFD)	MITSUBISHI / YASKAWA
R.P.M of Airend	3800 rpm
Drive System	Direct Driven with Frequency Controller
Outlet Connection & Cable Size	1 ¼" – (3x10)+6 + 6mm ²
Length	1400 mm
Width	1000 mm
Height	1335 mm
Weight	800 kg
Noise Level	**70 dB (A)
Max. Oil Content	2-3 ppm.(mg/m ³)
Warranty	Two Years Against Manufacturing Defects
Packing Weight & Dimension	850 kg – 1500 x 1100 x 1485 mm.

* FAD performance measured according to ISO 1217, Annex E – 2009

** Noise Level measured to ISO 2151, Tolerance ± 3 dB (A)

Lupamat reserves the right to make alterations on given data and compressor design without prior notice.

Lupamat

Makina Sanayii A.Ş.

