

SCREW AIR COMPRESSOR TECHNICAL SPECIFICATIONS

LUPAMAT LKV 45/7,5 DHK PREMIUM

DESCRIPTION	SPECIFICATIONS
Compressor Type	Oil Injected Screw Air Compressor
Max. Pressure	7,5 bar
Free Air Delivery (at 7,5 bar)*	8,9 m ³ /min.
Min. Pressure	5 bar
Min. Free Air Delivery	3,1 m ³ /min.
Shaft Power (at 7,5 bar)	52,8 kW
Max. Ambient Temperature	40°C
Electric Motor	45 kW / 60hp; 4 Pole (1480 rpm); 400V; 50Hz; IP55; F Insulation; B35 Built; IE4 Class; SF Motor
Cooling System	Air Cooling with Axial Fan
Fan Motor & Capacity	1.5 kW; (1435 rpm); 400V; 50Hz --- 7840/289 (m ³ /h)/Pa
Airend	VMX110 RD – AERZEN
Hydraulic Connections	VITILLO
Cooler	AKG
Oil & Air Filters	MANN+HUMMEL
Suction Control Group	EAGURT
Electric Components	MITSUBISHI / SCHNEIDER
Variable Frequency Drive(VFD)	MITSUBISHI / YASKAWA
Coupling	DODGE / REXNORD
R.P.M of Airend	2400 rpm
Drive System	Direct Driven with Frequency Controller
Outlet Connection & Cable Size	1 ½" --- (3x50)+25 mm ²
Length x Width x Height	1850 x 1250 x 1635 mm
Weight	1580 kg
Noise Level**	70 dB (A)
Max. Oil Content	2-3 ppm.(mg/m ³)
Warranty	Two Years Against Manufacturing Defects
Shipping Weight & Dimension	1630 kg. – 1950 x 1350 x 1800 mm

* FAD performance measured according to ISO 1217, Annex E – 2009

** Noise Level measured to ISO 2151, Tolerance ± 3 dB (A)

-Lupamat reserves the right to make alterations on given data and compressor design without prior notice.

Lupamat

Makina Sanayii A.Ş.


Lupamat
compressor




Lupamat
compressor