

SCREW AIR COMPRESSOR TECHNICAL SPECIFICATIONS

LUPAMAT LKV 90/7,5 DHK PLUS

DESCRIPTION	SPECIFICATIONS
Compressor Type	Oil Injected Screw Air Compressor
Max. Pressure	7,5 bar
Free Air Delivery (at 7,5 bar)*	14,25 m ³ /min
Min. Pressure	5 bar
Min. Free Air Delivery	5,5 m ³ /min
Power (at 7,5 bar)	90 kW
Max. Ambient Temperature	40 ⁰ C
Electric Motor	90 kW/125 hp; 2 Pole (2978 rpm); 400V; 50Hz; IP55; F Insulation; B35 Built; IE3 Class
Cooling System	Air Cooling with Axial Fan
Fan Motor & Capacity	5,5 kW; (1465 rpm); 400V; 50Hz -- 20051/407 (m ³ /h)/Pa
Airend	ITA18 – TMC
Hydraulic Connections	GURSAN / VITILLO
Oil & Air Filters	MANN+HUMMEL
Cooler	AKG
Suction Control Group	EAGURT
Electrical Supplies	SCHNEIDER / MITSUBISHI
Variable Frequency Drive(VFD)	MITSUBISHI / YASKAWA
Coupling	DODGE / REXNORD
R.P.M of Airend	5201 rpm
Driving	Direct Driven with Frequency Controller
Outlet Connection & Cable Size	2" --- (3x95)+50 mm ²
Length x Width x Height	3000 x 1800 x 2000 mm
Weight	3210 kg
Noise Level**	77 dB (A)
Max. Oil Content	2-3 ppm.(mg/m ³)
Warranty	Two Years Against Manufacturing Defects
Shipping Weight & Dimension	3220 kg – 3050 x 1850 x 2050 mm.

* FAD performance measured according to ISO 1217, Annex E-2009

** Noise Level measured to ISO 2151, Tolerance \pm 3 dB (A)

-Lupamat reserves the right to make alterations on given data & compressor design without prior notice.

Lupamat

Makina Sanayii A.Ş.

